

## DM - Manual Double vice

### Description




**Code:** *DM*

Additional vice for material locking.

## KIT G-Gravitational descent kit

### Description




**Code:** *KIT G*

The G optional allows to cut the material without the user's manual intervention through a manual operating lever.

## KIT PN-Pneumatic vice clamping

### Description



**Code:** *KIT PN*

With the PN optional the workpiece lock and unlock are made by a pneumatic vice.

A pneumatic circuit controls the needed compressed air (max 6 bar). You can read the working pressure on the pressure gauge.

## LX-Laser lighting for cutting line

### Description



**Code: LX**

The option LX facilitates the operator during the cutting phase: a luminous red line (laser light) is projected on the piece locked in the vice to exactly display where the blade will make the cut.

#### **NB1-One nozzle sprayer**

##### **Description**



**Code: NB1**

The band saw machine can be equipped of a blade and cutting cooling device. To improve the cutting quality and reduce pollution risk, moreover to avoid the risk of pools of cooling liquid on the floor (possible cause of accidental falls), the use of the NB optional is particularly suggested.

#### **VAT-Cutting angle display**

##### **Description**



**Code: VAT**

This optional allows to read, by means of a digital display, the cutting angle with an accuracy to tenths of a degree. With the graduated plate placed the standard machines, this is not possible. It also allows a good view of reading in low light.

#### **V-Blade rotation speed variator**

##### **Description**



**Code: V**

The V speed variator allows to constantly range the rotation blade speed from 20 to 100m /1' so giving the opportunity to choose the most suitable speed without causing any problem to the blade motor.