

## C2-Frame

### Description



**Code:** C2

It's a bar bearing support equipped with a roller. It can be used in addition to the roller table. It should be suitably ballasted or fixed to the floor. Roller 550 mm wide - max load 750 kg. H min 840 mm / H max 1.015 mm

## CREC-Loading side connection

### Description



**Code:** CREC

It's the loading side connection between machine and roller table specific for RE1G – RE2G roller tables.

## CRES-Connection in unloading side

### Description



**Code:** CRES

It's the unloading side connection between machine and roller table specific for RE1G – RE2G roller tables.

## FM..RSE-Length stop with articulated striker

### Description



**Code:** *FM..RSE*

The material must always be cut according to a prearranged length. The machine can be equipped of a length stop with a measure shaft from 1 to 6 meters specific for the RE1G-RE2G roller tables.

#### **RE1G-RE2G Roller tables**

##### **Description**



**Code:** *RE1G-RE2G*

RE1G-It's the one-meter roller table to be attached to the RE2G roller table or to another RE1G roller table previously attached to a RE2G roller table.  
RE2G-It's the one-meter roller table to be attached to the CREC and/or CRES optional connections.

#### **RM-Motorized roller**

##### **Description**



**Code:** *RM-Rullo motorizzato*

The RM motorized roller is generally placed near the band saw on the loading side; in this way the roller support surface is placed under the piece to be moved. Switching on the feeding selector, the roller automatically raises a few millimeters lifting the bar to be cut. Once the maximum quota is reached, the roller begins to turn moving the piece towards the selected direction: the selector turned anticlockwise makes the bar move backward, while turned clockwise makes it move forward. Releasing the selector, the roller automatically stops and goes down: so for its use the presence of an operator is always necessary. The roller rotation speed can be adjusted before or even during its moving (for instance going fast at the beginning and then slower during blade approach). Our motorized roller can be joined to all models of FMB band saws so that any movement is avoided during the cut. Its moving is electrical and its lifting power

is

1,500

kg.

**RRS-Unloading side pull-out roller surface**

**Description**



**Code:** *RRS*

It's the unloading side connection between machine and roller table.